

Technical Specifications for Wireless Keypad Model Reply® Interact



Enclosure

- Compact and rugged ABS blend case.
- Dimensions: 92 mm x 54 mm x 8 mm).
- Weight: Approx. 40 gramms
- Color: white plastic case with white membranes Other colors available on request
- Bails for Lanyards

User Identification

- Each keypad has an RF device identity ("address") between 1-400.
- Each keypad also has a unique device serial number.
 Serial numbers are permanent and set at manufacturing.
- Keypad Adress is submitted with each Vote

User Input

- 14 Keys.
 - ➤ Ten keys numbered 0-9 (A-J) In multidigit mode, up to 12 characters in length (ex. 45.067) may be input.
 - ➤ OK Key for confirmation
 - ➤ C Key for Clear/Cancel
- Entries can be "speed scored" to 0.02 second (20 millisecond) resolution to identify group response sequence ('fastest finger') during competitive events.

Display

- 6 Digit LC-Display, 38x16mm, Numbers 0 9 or Characters A – J
- Additional Icons: Signal strength, Send and receipt status, Battery Level
- A beep indicates a key press. Can be disabled via RF.

Power

- 2 Coin Cells CR 2032.
- The Auto power down functionality enables up to 15.000 Votes (Depending on Battery quality)
- Standby Time is 1 year (Depending on Battery quality)
- Battery Panel is secured by a screw

RF Technology

- Supports multiple channels, Two-way 2,4 GHz communication spread over 32 channels
- Security: Using a special RF Protocol for the keypads that ensures Data accuracy. Works also reliable within other 2.4GHz environments like Wi-Fi, PDA or mobile networks.
- After the keypad data has been successfully received by the basestation, the keypad will receive a confirmation.
- User friendly: Keypads and Basestation are linked. Therefore, changes on the Basestation are also applied to all its Keypads (e.g. Channel).
- All keypads can be checked simultaneously and submitting its status.

Range

Depending on Room constellation up to 70 x 70 m.

Speed

• 400 Keypads per Basestation within less than 5 seconds

Certificates

• FCC, IC and CE proofed.



Wireless Interactive Technology

Infowhyse GmbH Hermann-Ehlers-Strasse 8 61231 Bad Nauheim, Germany

Phone: +49 (6032) 9259280 Fax: +49 (6032) 92592829 Website: www.replysystems.com E-mail: sales@infowhyse.com

